

## ELYS TR FOOD



Track system, food product tailored CCT LED spotlight luminaire for horizontally positioned track installations. Simple beam direction adjustment with rotary driver box and spotlight head. Toolless exchangeable glass cover (protecting optic from dust) and 23°, 34° or 53° beam angle facet reflector. Track connector compatible with Eurotrack Plus / Stucchi / Nordic-Global tracks. Net luminous output up to 2750 lm, luminous efficiency up to 83 lm/W. 6 options of specific Correlated Colour Temperature (CCT) which enhance colours of particular food products (bakery, fresh meat, fresh fish and fruit). Guaranteed colour stability <math><3(4)</math> SDCM during entire service lifetime of 50 000 operating hours with failure rate L80 B10 at 35°C. Luminaire head made from die-cast aluminium, forged aluminium heatsink with 60% better performance compared to die-cast and extrusion technologies improves LED colour stability and lifetime. Structural powder coated white, grey or black surface finish. Thermally protected fixed or dimmable (1 – 100%, addressable DALI) driver built in quality die-cast aluminium driver box. Ambient operating temperature from 0°C to +35°C. Weight 1.1kg, dimensions (L x H x W) 172mm x 188mm x 135mm. Energy Efficiency Class (EEC) A+/A.