



INDUSTRY


NARROW 30°




MEDIUM 50°




MEDIUM WIDE 65°



OVAL



DIMENSIONS



- 8 years warranty
- LED
- up to 13000 lm
- up to 141 lm/W
- 70/80 Ra
- 3 SDCM

Mounting	Profile mounting (PM)
Optical system	Lenses: LSNA (NARROW 30°) LSME (MEDIUM 50°) LSMW (MEDIUM WIDE 65°) LSCO (OVAL)
Light distribution	Direct
Driver	Electronic control gear - FIX - DALI (dimnable 1-100%)
Materials	Housing: die cast AL Lenses: PMMA Cover: clear hardened glass
Surface finish	White (RAL 9003)
Weight	7.5 kg
Service lifetime	100 000 hours / L90 B10 @ 25°C 50 000 hours / L90 B20 @ 55°C
Ambient temperature	- 40 °C / + 55 °C
EEC	A++

PRELIMINARY

# GHADA-L

A definitive LED industrial luminaire with impressive parameters that can resist tough weather conditions. With its lifetime of up to 100,000 hours, reliable operability at high temperatures, a wide range of lumen outputs, excellent efficacies, and high IP and IK ratings, you will soon see the real value of this powerful luminaire.

Type	mounting type	modul	net lumen output (at Ta = 25 °C)	power consumption	color rendering index	correlated color temperature	optic	control	color
			(lm)	(W)	CRI (Ra)	CCT (K)			
GHADA-L	PM	NICHIA	13000	94	70	4000	30°/ 50°/ 65°/ OVAL	FIX / DALI	WHITE
GHADA-L	PM	NICHIA	13000	92	70	5000	30°/ 50°/ 65°/ OVAL	FIX / DALI	WHITE
GHADA-L	PM	NICHIA	13000	105	80	4000	30°/ 50°/ 65°/ OVAL	FIX / DALI	WHITE
GHADA-L	PM	NICHIA	13000	105	80	5000	30°/ 50°/ 65°/ OVAL	FIX / DALI	WHITE

Luminous flux tolerance +/- 10%. The Company reserves the right to change any product specifications without prior notification.

order description: GHADA-L PM N 13000 850 50 DA WH

STANDARD

