

EFFICIENT LIGHTING FOR CAR PARKS



Easy installation

Cover and the installation board can be dismantled without the use of any tools, electrical connection via push-in terminals.



Industry driver

It provides safe operation in wide range of ambient temperatures.


Modular line installation

The luminaire(s) can be installed on the profile mounting Smart-L system with the use of rail holders.




CAR PARK


FLANN




FLANN M



FLANN L



MOUNTING



5 years warranty

LED

up to 6950 lm/m

up to 136 lm/W

80 Ra



Mounting	Surface mounted (ceiling, wall), suspended
Optical system	Prismatic diffuser
Light distribution	Direct
Driver	Electronic control gear FIX / DALI (ECG / EDA) Through wiring (three options of phase connection - L1 / L2 / L3)
Materials	Clips: PC Diffuser: transparent injected PC + opal foil Installation plate: sheet steel Housing: grey injected polycarbonate
Surface finish	Installation plate: White (RAL 9003)
Accessories	On request: Rope suspension 020 (see accessories)
Service lifetime	50 000 hours / L80 B10 @ 40 °C
Ambient temperature	- 40 °C / + 40 °C
EEC	A++

FLANN

This industrial luminaire is a great fit for indoor parking areas. Not only has it high efficacies and various electrical options, it also provides for visual comfort without the risk of glare.

Type	mounting type	modul	net lumen output (at Ta = 25 °C)	power consumption	color rendering index	correlated color temperature	optic	control	color
			(lm)	(W)	CRI (Ra)	CCT (K)			
FLANN M	SM	LG	5400	41	80	3000K	PRISMA	FIX / DALI	GREY
FLANN M	SM	LG	5550	41	80	4000K	PRISMA	FIX / DALI	GREY
FLANN L	SM	LG	6750	51	80	3000K	PRISMA	FIX / DALI	GREY
FLANN L	SM	LG	6950	51	80	4000K	PRISMA	FIX / DALI	GREY

Luminous flux tolerance +/- 10%. The Company reserves the right to change any product specifications without prior notification.

STANDARD



order description: FLANN L SM LG 6950 840 PRIS DA GR