


DIMENSIONS



LED
up to
60
lm

Mounting	Wall Recessed
LED Device	high power OSRAM LEDs
LED color variants	3000K / 4000K / 5700K
Input Voltage	constant Voltage 12-24V DC
Wiring	electronic control gear intergated
Power cable connection	Outdoor cable H05RRR-F 2 x 1,5mm (L=0,5m)
Service lifetime	70,000 hrs / L70 @25°C
Operating ambient tem.	-20°C / +40°C
Materials	housing: die cast aluminium cover: Plastic
Dimensions	130 x 90 x 125 mm
Accessories (not included):	constant Voltage 12-24V Power supply

AEDI RECESSED 1

The stylishly modern and unassuming exterior of AEDI GLOBUS GROUND houses state-of-the-art white LED technology and made using the highest quality materials and construction methods. Bringing the flexibility to outdoor application, this powerful lighting fixture is ideally suited to use in landscape and building illumination, and IP65 ensures safe operation in even the most demanding areas.

Type	net lumen output (at Ta = 25 °C) (lm)	power consumption (W)	LED Device (LEDs Pcs.)	beam angle	weight (kg)
AEDI RECESSED 1	60	5	1	????	0.8

The Company reserves the right to change any product specifications without prior notification.

