



GLOBUS



SQUARE

LED  
up to  
100  
lm

Mounting	Ground recessed
LED Device	high power OSRAM LEDs
LED color variants	3000K / 4000K / 5700K / RED / GREEN / BLUE
Input Voltage	constant Voltage 12-24V DC
Wiring	electronic control gear intergated
Power cable connection	Outdoor cable H05RR-F 2 x 1,5mm (L=0,5m)
Service lifetime	70,000 hrs / L70 @25°C
Operating ambient tem.	-20°C / +40°C
Materials	housing: die cast aluminium cover: clear hardened glass
Dimensions	56 x 56 x 85 mm
Accessories (not included):	constant Voltage 12-24V Power supply

## AEDI GLOBUS RECESSED 1 AEDI SQUARE RECESSED 1

The stylishly modern and unassuming exterior of AEDI GLOBUS GROUND houses state-of-the-art White LED technology and made using the highest quality materials and construction methods. Bringing the flexibility to outdoor application, this powerful lighting fixture is ideally suited to use in landscape and building illumination, and IP67 ensures safe operation in even the most demanding areas.

Type	net lumen output (at Ta = 25 °C)	power consumption	LED Device	beam angle	weight
	(lm)	(W)	(LEDs Pcs.)		(kg)
<b>AEDI GLOBUS RECESSED 1</b>	100	1.2	1	Spot / Narrow / Medium / Wide / Asym.	0.3
<b>AEDI SQUARE RECESSED 1</b>	100	1.2	1	Spot / Narrow / Medium / Wide / Asym.	0.3

The Company reserves the right to change any product specifications without prior notification.

