



DIMENSIONS



LED

up to
2 x 600
lm



| | |
|-----------------------------|--|
| Mounting | Wall mounted |
| LED Device | high power OSRAM LEDs |
| LED color variants | 3000K / 4000K / 5700K |
| Input Voltage | constant Voltage 48V DC |
| Power cable connection | Outdoor cable H05RRR-F 2 x 1,5 mm (L=0,5m) |
| Service lifetime | 70,000 hrs / L70 @25°C |
| Operating ambient tem. | -20°C / +40°C |
| Materials | housing: die cast aluminium |
| Dimensions | 120 x 275 x 204 mm |
| Accessories (not included): | constant Voltage 48V Power supply |

AEDI WALL GLOBUS WHITE TWIN

The stylishly modern and unassuming exterior of AEDI GLOBUS houses state-of-the-art White LED technology and made using the highest quality materials and construction methods. Bringing the flexibility to outdoor application, this powerful lighting fixture is ideally suited to use in landscape and building illumination, and IP54 ensures safe operation in even the most demanding areas.

| Type | net lumen output (at Ta = 25 °C) (lm) | power consumption W (mA) | LED Device (LEDs Pcs.) | beam angle | weight (kg) |
|------------------------------------|---|-----------------------------|---------------------------|------------------------|----------------|
| AEDI WALL GLOBUS WHITE TWIN | 2x600 | 18.5 (500) | 2x6 | Spot / Narrow / Medium | 2.8 |

The Company reserves the right to change any product specifications without prior notification.

