




DIMENSIONS



MULTI STAR



STAR



up to
100
lm

| | |
|--------------------------------|--|
| Mounting | Ground Recessed |
| LED Device | high power OSRAM LEDs |
| LED color variants | 3000K / 4000K / 5700K / RED / GREEN / BLUE |
| Input Voltage | constant Voltage 48V DC |
| Wiring | electronic control gear intergated |
| Power cable connection | Outdoor cable H05RR-F 2 x 1,5mm (L=0,5m) |
| Service lifetime | 70,000 hrs / L70 @25°C |
| Operating ambient tem. | -20°C / +40°C |
| Materials | housing: die cast aluminium |
| Dimensions | ø170 x 147 mm |
| Accessories (not included): | constant Voltage 48V Power supply |

AEDI MULTI STAR GROUND AEDI STAR GROUND

The stylishly modern and unassuming exterior of AEDI GLOBUS GROUND houses state-of-the-art LED technology and made using the highest quality materials and construction methods. Bringing the flexibility to outdoor application, this powerful lighting fixture is ideally suited to use in landscape and building illumination, and IP67 ensures safe operation in even the most demanding areas.

| Type | net lumen output (at Ta = 25 °C) | power consumption | LED Device | beam angle | weight |
|-------------------------------|-------------------------------------|----------------------|---------------|---------------|--------|
| | (lm) | W | (LEDs Pcs.) | | (kg) |
| AEDI MULTI STAR GROUND | 100 | 5 | 4 | Multi Star | 2,1 |
| AEDI STAR GROUND | 100 | 5 | 1 | Star | 2,1 |

The Company reserves the right to change any product specifications without prior notification.

